UP-CN01 Casambi Ready Wireless Controller for 3-Pin Twist M52 Receptac



UP-CN01 is a CASAMBI ready wireless control device for LED driver. The device is mainly used in LED luminaires and has 0-10V, 1-10V dimming interfaces. The device can form a secure wireless network with a smart phone or smart tablet through Bluetooth technology, so as to control a large number of LED luminaires and does not require an external gateway module.
Wireless controllable with a Android / iOS smart device
No external or collocation gateway is required
Forms automatically a wireless communication network with up to 250 nodes
Analog output: 0-10V/1-10V
Device firmware can be updated over-the-air
5-year guarantee
Applications:
LED high bay, LED linear light, LED linear high bay, LED panel light

ADDITIONAL PRODUCT SPECIFICATIONS

UP-CN01 is a CASAMBI ready wireless control device for LED driver. The device is mainly used in LED luminaires and has 0-10V, 1-10V dimming interfaces. The device can form a secure wireless network with a smart phone or smart tablet through Bluetooth technology, so as to control a large number of LED luminaires and does not require an external gateway module. Wireless controllable with a Android / iOS smart device No external or collocation gateway is required Forms automatically a wireless communication network with up to 250 nodes Analog output: 0-10V/1-10V Device firmware can be updated over-the-air 5-year guarantee Applications: LED high bay, LED linear light, LED linear high bay, LED panel light

PRODUCT VIEWS



VIEW 1



VIEW 2



VIEW 3