

KIRITO

ADDITIONAL PRODUCT SPECIFICATIONS

Series Code	FL23
Power	50W, 100W, 150W, 200W, 300W, 400W, 500W
Efficacy	125lm/W, 130lm/W, 140lm/W
Input Voltage	220-240VAC, 50 / 60 Hz
Power Factor	>0.90, >0.95
CCT	3000K, 4000K, 5000K
CRI(Ra)	70, 80
Control	1-10V Dimmable
Class Electrical Equipment	Class I / II optional
IP Rating	IP66
IK Rating	IK08
Mounting Option	Bracket Mounting
Warranty	5 Years
Surge Protection	6kV-20kV
Operating Temperature	-30°C to + 50°C

The product has been discontinued online. Please contact our sales representative for more information. FL23 anti-corrosion version is aimed at seaside applications. Its specially adapted surface treatment provides excellent anti-corrosion ability. It can be applied in chemical plants, swimming pools, coastal ships, and boatyards. Bright, robust, and durable Marine-grade lighting solution Asymmetric, wide, and narrow optics are optional Mechanical housing Die-cast ALU by electrophoresis + special powder coating. Metallic parts Screws are all made of anti-corrosive material, surface treated by GEOMET technology. Mounting bracket Top-quality anti-corrosive material with KIRITO's special powder coating. Applications: Seaside, Coastal areas, Swimming pool, Chemical Plants, Stadium, Parking lot.

PRODUCT VIEWS



VIEW 1



VIEW 2



VIEW 3



VIEW 4