KIRITO



WP22 AmbriLux

Low Glare Wall Pack Light

Sleek and contemporary design, for urban wall mounted, public places or paths.

- IP66
- IK10
- Power selectable
- CCT selectable
- 0-10V
- DALI 2.0
- Easy stock

Durable Material & High Protection Rating

Aluminium alloy + Polycarbonate, achieving IP66 waterproof rating and IK10 impact resistance.

IP66 IK10






Save SKU & Energy

5 power & 2 CCT selectable via dip-switch: reduces SKU inventory and enables energy-saving operation, thus supporting fast delivery.


Power selectable








CCT selectable







Easy Maintenance

Driver and LED modules support independent replacement with simple steps, helping reduce maintenance costs.



Soft & Low-Glare Ambient Lighting

It delivers premium low-glare illumination with a milky PC diffuser for enhanced visual comfort and soft lighting as an ideal ambiance enhancement.

ADDITIONAL PRODUCT SPECIFICATIONS

Series Code	WP22
Power	20W
Efficacy	105lm/W
Input Voltage	220-240VAC, 50 / 60 Hz
Power Factor	>0.90
CCT	3000K, 4000K
CRI(Ra)	70, 80
Corrosion Class	C3
Class Electrical Equipment	Class I
IP Rating	IP66
IK Rating	IK10
Mounting Option	Wall
Warranty	5 Years
Operating Temperature	-30°C to + 45°C

AmbriLux is a sleek, low-glare wall pack light designed for urban and public spaces. 5 power and 2 CCT adjustable options help reduce SKUs and support fast delivery. The aluminum alloy housing, combined with a polycarbonate diffuser, achieves IP66 and IK10 ratings for reliable outdoor performance. Independent, replaceable driver and LED modules enable fast and easy maintenance.

PRODUCT VIEWS



VIEW 1



VIEW 2



VIEW 3