NIKKON®

DRACO HELÓ HIGHBAY



HELÓ 50W



HELÓ 100W

LUMINAIRE SPECIFICATIONS

- **Power** 50W 100W
- **Fitting Material** Non-Corrosive Die-Cast Aluminium
- **Fitting Color** Black
- **Optical Cover** Transparency Tempered Glass
- **Ingress Protection** IP65
- **Impact Protection** IK08
- **Voltage** 220 ~ 240 Vac 50 / 60Hz
- **Electrical Safety Class** Class I
- **Light Efficiency** >100 lm/W
- **Power Factor** >0.9
- **Operating Temperature** -30 ~ +45ºC
- **Installation** Hook Mounting
- **Surge Protections** Yes, 4kV
- **Pre-Wire** 300 mm

APPLICATION

- Eateries, Retails, Hallways, Storage Rooms, Halls & Factories

LED MODULE SPECIFICATIONS

- **Color Temperature** 5700K Daylight
- **Color Rendering Index (CRI)** >70
- **L70** 100,000 Hrs @ 25ºC
- **PCB Material** Metal Core

FEATURES

- Built-In IC Technology
- Direct AC Supply Connection (220 ~ 240 Vac 50 / 60Hz)
- No External Driver Required
- High System Efficiency
- Mid Power LEDs
- Thin & Lightweight Size
- Safety Wire
- External Surge Protection Devices (SPD)

COMPLIANCE STANDARD

- **LED** LM80
- **Luminaire** EN60598-1, EN60598-2-1, EN55015, EN61547, EN61000

CE


MEASUREMENT & ORDER CODE


WATTAGE	ORDER CODE	TYPICAL LUMINOUS FLUX	TYPICAL WATTAGE	CARTON DIMENSION (L x W x H) mm	NETT WEIGHT
50W	K14110 HELÓ 50W	5000	50	205 x 94 x 205	1.0 kg
100W	K14111 HELÓ 100W	10000	100	265 x 103 x 265	1.9 kg




DIMENSION


HELÓ 50W






HELÓ 100W






PHOTOMETRIC

HELÓ 50W



HELÓ 100W



Note: All specifications are subject to change without prior notice for product improvement. Images are for illustrative purposes only.

NIKKON®

DRACO HELÓ HIGHBAY



HELÓ 150W



HELÓ 200W

LUMINAIRE SPECIFICATIONS

- **Power** 150W 200W
- **Fitting Material** Non-Corrosive Die-Cast Aluminium
- **Fitting Color** Black
- **Optical Cover** Transparency Tempered Glass
- **Ingress Protection** IP65
- **Impact Protection** IK08
- **Voltage** 220 ~ 240 Vac 50 / 60Hz
- **Electrical Safety Class** Class I
- **Light Efficiency** >100 lm/W
- **Power Factor** >0.9
- **Operating Temperature** -30 ~ +45ºC
- **Installation** Hook Mounting
- **Surge Protections** Yes, 8kV
- **Pre-Wire** 300 mm

APPLICATION

- Warehouses, Multipurpose Halls, Exhibition Halls, Production Areas & Factories

LED MODULE SPECIFICATIONS

- **Color Temperature** 5700K Daylight
- **Color Rendering Index (CRI)** >70
- **L70** 100,000 Hrs @ 25ºC
- **PCB Material** Metal Core

FEATURES

- Built-In IC Technology
- Direct AC supply Connection (220 ~ 240 Vac 50 / 60Hz)
- No External Driver Required
- High System Efficiency
- Mid Power LEDs
- Thin & Lightweight Size
- External Surge Protection Devices (SPD)

COMPLIANCE STANDARD

- **LED** LM80
- **Luminaire** EN60598-1, EN60598-2-1, EN55015, EN61547, EN61000

CE


MEASUREMENT & ORDER CODE


WATTAGE	ORDER CODE	TYPICAL LUMINOUS FLUX	TYPICAL WATTAGE	CARTON DIMENSION (L x W x H) mm	NETT WEIGHT
150W	K14112 HELÓ 150W	15000	150	330 x 135 x 330	3.2 kg
200W	K14113 HELÓ 200W	20000	200	390 x 135 x 390	4.2 kg




DIMENSION


HELÓ 150W






HELÓ 200W






PHOTOMETRIC

HELÓ 150W



HELÓ 200W



Note: All specifications are subject to change without prior notice for product improvement. Images are for illustrative purposes only.