NIKKON®

ZULO II FLOODLIGHT



ZULO II 50W



ZULO II 100W



ZULO II 200W

LUMINAIRE SPECIFICATIONS

- **Power** 50W 100W 200W
- **Fitting Material** ADC12 Die-Cast Aluminium Non-Corrosive
- **Fitting Color** Black
- **Optical Cover** Clear Glass
- **Ingress Protection** IP66
- **Impact Protection** IK08
- **Voltage** 220 ~ 240 Vac 50 / 60Hz
- **Electrical Safety Class** Class I
- **Operating Temperature** -40 ~ +45ºC
- **Installation** Mounting Bracket
- **Surge Protections** Yes, 8kV

APPLICATION

- Exhibition Halls, Car Park, Walkways, Sport Fields, Billboards & Construction Sites

LED MODULE SPECIFICATIONS

- **Color Temperature** 3000K Warm White 6500K Daylight
- **Color Rendering Index (CRI)** >70
- **L70** 100,000 Hrs @ 25ºC

FEATURES

- Built-In IC Technology
- Direct AC Supply Connection (220 ~ 240 Vac 50 / 60Hz)
- No External Driver Required
- High System Efficiency
- Mid Power LEDs
- Thin & Lightweight Size

COMPLIANCE STANDARD

- **LED** LM80
- **Luminaire** EN60598-1, EN60598-2-1, EN62471, EN62493, EN61000-3, EN61547, EN55015

CE

MEASUREMENT & ORDER CODE


WATTAGE	ORDER CODE	TYPICAL LUMINOUS FLUX	TYPICAL WATTAGE	QTY/CARTON	NETT WEIGHT (PER UNIT)	CARTON DIMENSION (L x W x H) mm
50W	Zulo II 50W	4941	50W	20pcs/ctn	0.9 kg	445 x 360 x 230
100W	Zulo II 100W	10506	100W	10pcs/ctn	2.0 kg	420 x 315 x 315
200W	Zulo II 200W	20160	200W	5pcs/ctn	3.3 kg	390 x 270 x 390

* Please indicate LED color temperature when ordering.
* All result tested base on 6500K CCT LEDs.




DIMENSION


ZULO II 50W



ZULO II 100W




ZULO II 200W




PHOTOMETRIC


ZULO II 50W



ZULO II 100W



ZULO II 200W



Note: All specifications are subject to change without prior notice for product improvement. Images are for illustrative purposes only.

NIKKON®

ZULO II FLOODLIGHT



ZULO II 300W



ZULO II 400W

LUMINAIRE SPECIFICATIONS

- **Power** 300W 400W
- **Fitting Material** ADC12 Die-Cast Aluminium Non-Corrosive
- **Fitting Color** Black
- **Optical Cover** Clear Glass
- **Ingress Protection** IP66
- **Impact Protection** IK08
- **Voltage** 220 ~ 240 Vac 50 / 60Hz
- **Electrical Safety Class** Class I
- **Operating Temperature** -40 ~ +45ºC
- **Installation** Mounting Bracket
- **Surge Protections** Yes, 8kV

APPLICATION

- Exhibition Halls, Car Park, Walkways, Sport Fields, Billboards & Construction Sites

LED MODULE SPECIFICATIONS

- **Color Temperature** 3000K Warm White 6500K Daylight
- **Color Rendering Index (CRI)** >70
- **L70** 100,000 Hrs @ 25ºC

FEATURES

- Built-In IC Technology
- Direct AC Supply Connection (220 ~ 240 Vac 50 / 60Hz)
- No External Driver Required
- High System Efficiency
- Mid Power LEDs
- Thin & Lightweight Size

COMPLIANCE STANDARD

- **LED** LM80
- **Luminaire** EN60598-1, EN60598-2-1, EN62471, EN62493, EN61000-3, EN61547, EN55015

CE

MEASUREMENT & ORDER CODE


WATTAGE	ORDER CODE	TYPICAL LUMINOUS FLUX	TYPICAL WATTAGE	QTY / CARTON	NETT WEIGHT (PER UNIT)	CARTON DIMENSION (L x W x H) mm
300W	Zulo II 300W	28823	300W	2pcs/ctn	4.9 kg	455 x 128 x 455
400W	Zulo II 400W	38125	400W	2pcs/ctn	7.0 kg	515 x 140 x 515

* Please indicate LED color temperature when ordering.
* All result tested base on 6500K CCT LEDs.




DIMENSION

ZULO II 300W




ZULO II 400W




PHOTOMETRIC

ZULO II 300W



ZULO II 400W



Note: All specifications are subject to change without prior notice for product improvement. Images are for illustrative purposes only.